

Model No.			CLT-35W	CLT-72W	CLT-100W	CLT-120W
Power Supply: 220-240/380VAC, 1/3PH,50hz						
Performance						
Capacity	Cooling	Btu/h	12000	24000	36000	41000
		W	3500	7200	10000	12000
	Heating	Btu/h	13000	27000	40000	46000
		W	3800	7900	12000	14000
	Water Tank Hot Water	L	150	260	300	500
L		280	500	600	1000	
indoor type			wall mount	wall mount	duct type	duct type
Air Circulation		m ³ /h	550	1050	1700	1800
Suitable Area		m ²	15~23	30~48	42~67	50~80
EER		W/W	3.89	3.82	3.87	3.96
Noise	Indoor	dB(A)	≤42	≤50	≤51	≤53
	Outdoor	dB(A)	≤52	≤58	≤58	≤60
Hot Water Temp		°C	50~90	50~90	50~90	50~90
Solar Collector		Vacuum Tube	18*1	24*1	18*2	24*2
Power Consumption						
Power Input	Cooling	W	800~1025	1700~1900	2400~2640	2900~3150
	Heating	W	800~1050	1700~1950	2470~2650	2900~3180
Rated Current	Cooling	A	3.64~4.66	7.73~8.64	10.91~11.95	13.18~14.32
	Heating	A	3.64~4.77	7.73~8.66	10.91~12.05	13.18~14.45



REMARKS:

Parameters in the form are measured in the rated working state according to GB/T7725-2004. Changes may appear according to real working state.

Parameters may change due to the product improvement, please refer to the products nameplate.

If the indoor type or the water tank capacity can't meet your requirement, please kindly contact us for a new quotation

There are 3 heat exchange copper coil inside the water tank.